


# InterSense® IS-900 Systems **6-DOF Motion Tracking System**



Precision Inertial-Ultrasonic  
Hybrid Tracking Technology

# InterSense® IS-900 Systems

InterSense® IS-900 6-Degrees of Freedom (DOF) tracking systems feature an innovative hybrid inertial-ultrasonic technology that delivers real-time orientation and position tracking, and eliminates noticeable jitter and latency for the smoothest, most realistic visual experience possible. Furthermore, the IS-900's inertial-ultrasonic technology is immune to electromagnetic and metallic interference, so users can focus intently on their mission without constant re-calibration and re-mapping.



## Technical Specifications

### Key Features

- ▶ Highly Flexible, Configurable and Extensible.
- ▶ Wired and Wireless Tracking Options.
- ▶ OEM Tracker Kits with Optional GPIO.
- ▶ Information Assurance Compatible.

### Physical Specifications

**AC Input:** 100 – 240 V, 1A, 50/60Hz, (auto switching)

**Operating Temperature:** 0 to 40° C

**Storage Temperature:** -20 to 70° C

**Standard Cable Lengths:** 9.4 m (IS-900 to SoniStrips); 10.0 m (IS-900 to Tracking Devices); 1.8 m (IS-900 to Host, RS-232 Serial)

**Maximum Cable Lengths:** Contact your Thales InterSense Representative

**Processor Size:** 1 U rack mounted (44.45 cm wide x 40.64 cm deep x 4.45 cm tall)

**Processor Weight:** 6.8 kg

### Performance Specifications

**Degrees of Freedom:** 6 (X, Y, Z, Yaw, Pitch, and Roll)

**Tracking Devices:** MicroTrax Head Tracker; MicroTrax Wand; MicroTrax Hand Tracker; Custom/OEM MicroTrax Devices (Contact your Thales InterSense Representative)

**Tracking Volume:** Up to 20 m<sup>2</sup> with 12 SoniStrips (SimTracker); Up to 140 m<sup>2</sup> with 84 SoniStrips (VETracker); SoniFrame – 2.0 m x 2.0 m x 3.0 m; SoniWing – 1.0 m x 1.0 m x 1.0 m

**Angular Range:** Full 360° – all axis

**Resolution:** 0.75 mm (1.5 mm Wireless); 0.05° (0.10° Wireless)

**Static Accuracy\* (wired):** 2.0 – 3.0 mm; 0.25° RMS in Pitch & Roll, 0.50° RMS in Yaw

**Static Accuracy\* (wireless):** 3.0 – 5.0 mm; 0.50° RMS in Pitch & Roll, 1.00° RMS in Yaw

**Update Rate:** 180 Hz Nominal (120 Hz Nominal Wireless)

**Latency:** 4 ms Typical

**Interface:** Ethernet; RS-232 Serial Port

**Maximum Number of Devices:** 4 for SimTracker, 7 for VETracker

**Prediction:** Up to 50 ms

**Genlock Synchronization:** Yes

### Software Support

SDK with full InterSense API for Windows and Linux

ISDEMO control and connectivity software

\*Accuracy specifications are measured in a controlled environment and are subject to change for custom configurations.

Specifications are subject to change without notice.

### Thales Visionix

Division of Thales Defense & Security, Inc.

700 Technology Park Drive, Suite #102 | Billerica, MA 01821

P: +1.781.541.6330 | E-mail: info@thalesvisionix.com

www.intersense.com | www.thalesdsi.com



2605:072020:V2

Thales has a policy of continuous development and improvement and consequently the equipment may vary from the description and specification in this document. This document may not be considered as a contract specification. Graphics do not indicate use or endorsement of the featured equipment or service. Copyright © 2020 Thales